

Excavators / E32 Compact Excavator Specifications & Options

Standard
 Optional
 N/A Not Applicable

Units US

| Configuration | Bobcat E32 25 HP | | |
|----------------------|------------------|-----------|-----------|
| | E32R Std Arm | E32R (EA) | E32R (LA) |
| Emissions Tier (EPA) | Tier 4 | Tier 4 | Tier 4 |
| Engine Fuel | Diesel | | |
| Maximum Governed RPM | 2,200 rpm | 2,200 rpm | 2,200 rpm |
| Horsepower | 24.8 hp | 24.8 hp | 24.8 hp |
| Turbocharged Engine | N/A | N/A | N/A |
| Optional Horsepower | n/a | | |

Performance

| | | | |
|-------------------------------|-----------|-----------|-----------|
| Operating Weight | 7,340 lb | 8,434 lb | 8,203 lb |
| Weight Class | 3.3 t | 3.8 t | 3.7 t |
| Travel Speed - High | 2.9 mph | 2.9 mph | 2.9 mph |
| Travel Speed - Low | 1.6 mph | 1.6 mph | 1.6 mph |
| Arm Digging Force | 4,859 lbf | 4,478 lbf | 3,986 lbf |
| Bucket Digging Force | 6,969 lbf | 6,968 lbf | 6,968 lbf |
| Rated Lift Capacity | 2795 lb | 2564 lb | 2702 lb |
| Lift Radius | 118 in | | |
| Boom Swing - Left | 75° | | |
| Boom Swing - Right | 55° | | |
| Maximum Dig Depth | 10.2 ft | 12.9 ft | 11.2 ft |
| Max Dump Height | 11 ft | 12.5 ft | 11.5 ft |
| Maximum Reach at Ground Level | 16.3 ft | 18.9 ft | 17.4 ft |

Capacities

| | |
|-----------|----------|
| Fuel Tank | 13.7 gal |
|-----------|----------|

Hydraulic System

| | | | |
|--------------------|--------------|-----------|-----------|
| Auxiliary Std Flow | 16.9 gal/min | | |
| Auxiliary Pressure | 2,987 psi | 2,987 psi | 2,987 psi |

Dimension

| | | | |
|-----------------------------------|----------|----------|----------|
| Length | 183.5 in | 187.7 in | 187.5 in |
| Overall Length in Travel Position | 183.5 in | 187.7 in | 187.5 in |
| Width | 61 in | 61 in | 61 in |
| Height | 96.2 in | 96.2 in | 96.2 in |
| Height with Operator Cab | 96.2 in | 96.2 in | 96.2 in |

Features

| | | | |
|--|-------------------------------------|-------------------------------------|-------------------------------------|
| Air Conditioning | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| Cab Enclosure | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| Cab Heater | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| Heater Air Conditioning | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| Radio | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| Tail Swing Type | Conventional | Conventional | Conventional |
| Engine Shutdown | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| Auxiliary Hydraulics | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| Secondary Auxiliary Hydraulics | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> | <input checked="" type="checkbox"/> |
| Quick Tach System | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| Rubber Track | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| Selectable Auxiliary Hydraulic Flow | <input type="checkbox"/> | <input type="checkbox"/> | <input type="checkbox"/> |
| Angle Blade | N/A | N/A | N/A |

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.