

SILAGE DEFACER

AD7 | AD11



JOHN DEERE



Silage Defacer

AD7 | AD11



Specifications

- Allows removal of haylage and silage from feed bunkers.
- Loosens materials while maintaining a smooth, compacted bunker space.
- Pierces, separates, and rakes without cutting or reducing the size of the material.
- Unique blade design and configuration ensure complete blending.
- Open design/construction enables expansive operator visibility and provides adjustable guides for depth of cut.
- Like all Worksite Pro™ attachments these silage defacers are compatible with John Deere skid steers, compact track loaders (CTLs), and compact wheel loaders (CWLs) equipped with a skid-steer-style Quick-Tatch™ coupler.

	AD7	AD11
Cutting Width	2460.6 mm (96.9 in.)	2460.6 mm (96.9 in.)
Depth of Cut	0–76.2 mm (0–3 in.)	0–76.2 mm (0–3 in.)
Reach	2.13 m (7 ft.)	3.35 m (11 ft.)
Weight	413 kg (910 lb.)	470 kg (1,037 lb.)
Hydraulic Flow	60.6–94.6 L/min. (16–25 gpm)	60.6–94.6 L/min. (16–25 gpm)
Vehicle Compatibility	312GR, 314G, 316GR, 318G, 320E, 324E, 330G, and 332G Skid Steers; 317G, 323E, 331G, and 333G CTLs; and 204K, 244K-II, 304K, and 324K CWLs	320E, 324E, 330G, 332G Skid Steers; 323E, 331G, and 333G CTLs; and 204K, 244K-II, 304K, and 324K CWLs

WORKSITE PRO™

This literature has been compiled for worldwide circulation. While general information, pictures, and descriptions are provided, some illustrations and text may include finance, credit, insurance, product options, and accessories NOT AVAILABLE in all regions. PLEASE CONTACT YOUR LOCAL DEALER FOR DETAILS. John Deere reserves the right to change specifications, design, and price of products described in this literature without notice.

